

Gazpromneft PM

Process Oil

PRODUCT DESCRIPTION

Designed to meet the needs of rubber manufacturing industry **Gazpromneft PM** process oil is produced from sweet crude oil distillates via the solvent extraction, dewaxing and hydrotreating processes.

APPLICATION

The product is intended for use in tire manufacturing and other technical rubber goods production.

TYPICAL PROPERTIES

Viscosity, cSt @ 40°C	32
Viscosity, cSt @ 100°C	5.3
VI	96
Flash Point, COC, °C	226
Pour Point, °C	-23
Aniline Point, 100°C	100.4
Color	0.5

HEALTH AND SAFETY

When used as directed, Gazpromneft PM has no adverse effects on health. The oils refer to Hazard Class 4, and to Hazard Class 3 as oil mist (GOST 12.1.007). Avoid contact with skin. Wear protective gloves. In case of contact, flush immediately with water and soap.

Use the product according to its intended purpose. Gazpromneft PM process oil is flammable liquid with flash point not less than 205°C. Observe all of laws, rules, regulations and agreements relevant to the environment. Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.

Manufacturer: Gazpromneft-Lubricants Ltd. 125A Profsoyuznaya St., Moscow 117647 Russia; Gazpromneft Omsk Lubricants Plant, 1 Pr. Gubkina, Omsk 644040 Russia.

For more information please contact our technical personnel: e-mail: Techservice@gazprom-neft.ru.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

12.07.2013

